






Bond Street  
Elevation (West)



Chandos Street  
Elevation (South)



West Quay Elevation (East)



T: 07951 742515  
E: james@restorationdesignstudio.co.uk  
W: www.r-designstudio.co.uk

Project:	Scale:	1:100 @ A1	Revisions:
	Date:	January 2016	
	DWG No.	062015/02	
	Author:	James Kinnear	
Drawing:	Existing Elevations	Client:	




A1	1:100
----	-------

Property Schedule:


Unit 1 - 70.3m <sup>2</sup>	Unit 5 - 75.6m <sup>2</sup>	Unit 9 - 67.5m <sup>2</sup>
Unit 2 - 76.6m <sup>2</sup>	Unit 6 - 66.4m <sup>2</sup>	Unit 10 - 64.5m <sup>2</sup>
Unit 3 - 56.7m <sup>2</sup>	Unit 7 - 82m <sup>2</sup>	Unit 11 - 28.4m <sup>2</sup>
Unit 4 - 90.2m <sup>2</sup>	Unit 8 - 72.8m <sup>2</sup>	Unit 12 - 29.5m <sup>2</sup>

SCALE




0 2 4 6 8 10 12



## West Quay Street-Side Ground Floor



Bond Street-Side Ground Floor/  
West Quay First Floor



Bond Street First Floor/  
West Quay Second Floor



Project: Wessex House 12 – 14 West Quay Bridgwater Somerset TA6 3HW	Scale: 1:100 @ A1 / 1:200 @ A3
	Date: June 2015
	DWG No. 062015/05X1
	Author: James Kinnear
Drawing: Proposed Floor Plans	Client: Energy Drop Zone Ltd



Revisions:

- A - 18/07/16 - Dimensions added, slight internal layout changes to units and unit 10 overhaul. Changed dimensions to units 3, 9, 10, 11 & 12 to as-built dimensions and modifications.
- B - 21/07/16 - Some bathroom layouts changed to suit stack locations, added electrical layouts, changed fire alarm layouts, further as-built and design-stage minor layout changes, unit 3 KLD layout reversed for drainage.
- C - 24/7/16 - Added 4 x en-suites to units 4, 5, 3 and 10. Changed office area to gym including structural changes and use of space in the bonded warehouse.
- D - 01/12/16 - Additional en-suites added and layouts amended.
- E - 15/06/17 - Gym fire alarm system added and minor BReg amendments as per email discussions.



Whilst the greatest of care has been taken to ensure the accuracy of these dimensions, please be aware that they may vary on-site.


A2 1:100




EAST ELEVATION



WEST ELEVATION



SOUTH ELEVATION




NORTH ELEVATION




T: 07951 742515  
E: james@restorationdesignstudio.co.uk  
W: www.r-designstudio.co.uk

Project:	Scale:	1:100 @ A2	Revisions:
	Date:	October 2016	
	DWG No.	102016/E2	
	Author:	James Kinnear	
Drawing:	Proposed Elevations	Client:	



A2 1:100

Whilst the greatest of care has been taken to ensure the accuracy of these dimensions, please be aware that they may vary on-site.



EXISTING FOUL DRAINAGE ROUTE

SECTION A-A

A

REAR / CAR PARK ENTRANCE

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59

60

61

62

63

64

65

66

67

68

69

70

71

72

73

74

75

76

77

78

79

80

81

82

83

84

85

86

87

88

89

90

91

92

93

94

95

96

97

98

99

100

101

102

103

104

105

106

107

108

109

110

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

126

127

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

144

145

146

147

148

149

150

151

152

153

154

155

156

157

158

159

160

161

162

163

164

165

166

167

168

169

170

171

172

173

174

175

176

177

178

179

180

181

182

183

184

185

186

187

188

189

190

191

192

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

210

211

212

213

214

215

216

217

218

219

220

221

222

223

224

225

226

227

228

229

230

231

232

233

234

235

236

237

238

239

240

241

242

243

244

245

246

247

248

249

250

251

252

253

254

255

256

257

258

259

260

261

262

263

264

265

266

267

268

269

270

271

272

273

274

275

276

277

278

279

280

281

282

283

284

285

286

287

288

289

290

291

292

293

294

295

296

297

298

299

300

301

302

303

304

305

306

307

308

309

310

311

312

313

314

315

316

317

318

319

320

321

322

323

324

325

326


327

328

329

330





Materials Key:

1. 100mm existing rigid PIR insulation

2. Existing timber roof truss rafters, breather membrane, battens and slate tiles.

3. Existing 12.5mm plasterboard, skimmed and painted.

4. 22mm T&G chipboard flooring.

5. Instacoustic floating floor system or similar.

6. Existing floorboards.

7. Existing 220x50-70mm solid timber floor joists (estimated by floor thickness).

8. Existing lathe and plaster ceiling.

9. 12.5mm Gyproc Fireline board.

10. IN10 acoustic insulation.

11. 2 x layers of 12.5mm Gyproc Fireline.

12. Isolation washer.

13. Adjustable acoustic hanger.

14. 100mm Rockwool insulation or similar.

15. 50mm fibreglass or rockwool insulation between 75mm timber stud at 400 centres.

16. 50mm fibreglass or rockwool insulation
- between existing 125x50mm timber stud or new timber stud min 75x50mm.

17. 2 layers of 15mm Gyproc Soundbloc.

18. 75mm Isover APR 1200 acoustic insulation between existing 125mm timber stud.

19. Gypframe RB1 resilient bar at 600 centres.

20. Existing brick masonry cavity wall.

21. Celotex PL4000 composite insulation board or similar system at 62.5mm thickness. (unless cavity has been filled with insulation previously, in which case not added).

22. Preformed tread and nosing fitted with counter sunk screws and acoustic sealant at specific intervals (see Building Regulation notes for details.)

23. InstaCoustic Sound Barrier with grooved section round nosing.

24. Existing timber stairs.

25. Countersunk head screws.

26. Cavity fill blown insulation to suitable
- specification following cavity survey.

27. Double glazed timber frame sash window.

28. Existing masonry cavity closer.

29. Existing heavy duty fibreglass roof covering, repaired where necessary.

30. Existing 240x75mm timber joists.

31. 300x152mm Existing steel I beam

32. Existing imber supports connecting steel beams to joists.

33. Rooflights to client's specification and installed to manufacturer's detailing.

34. Timber fillets 250-0mm

35. Upstand/flashing between roof and new timber frame wall.

36. Existing 152x152mm steel columns.

37. Vapour control layer

38. 140x47mm CLS timber stud at 400 centres as per structural engineer's calculations/design, with min. 120mm Celotex rigid PIR insulation or similar between studs.
39. 11mm OSB sheathing.

40. Breather membrane.

41. 25x38mm vertical treated timber battens.

42. Cement board and render.

43. Parapet flashing.

44. 180x50mm solid timber flat roof joists.

45. EPDM roofing system installed as per manufacturer's details.

46. 300mm fibreglass quilt or other suitable insulation to achieve max. 0.16W/m2K

47. New 185x75mm solid timber floor joists.

48. RSJ as per structural engineer's calculations and design to support proposed timber frame extension where necessary and remaining pitched roof trusses.

49. Existing double glazed openable rooflight.


50. Window reveals insulated with Celotex PL4000 composite board or equivalent system with 25mm thickness, unless existing timber window sills and frames to be retained.




T: 07951 742515  
E: james@restorationdesignstudio.co.uk  
W: www.r-designstudio.co.uk

Project:	Scale:	1:50 @ A2	Revisions:
	Date:	November 2016	
	DWG No.	102016/S3	
	Author:	James Kinnear	
Drawing:	Proposed Section	Client:	







Whilst the greatest of care has been taken to ensure the accuracy of these dimensions, please be aware that they may vary on-site.




ROOF PLAN



SECOND FLOOR




FIRST FLOOR



NORTH WEST ELEVATION




NORTH EAST ELEVATION




SOUTH EAST ELEVATION



SOUTH WEST ELEVATION



GROUND FLOOR PLAN



PORCH ELEVATIONS



T: 07951 742515  
E: james@restorationdesignstudio.co.uk  
W: www.r-designstudio.co.uk  
ARCHITECTURE & PROPERTY DEVELOPMENT




PLUMBING | HEATING | ELECTRICAL | RENEWABLE ENERGY

T: 01935 423006  
E: admin@bamfordsyeovil.com  
F: www.bamfordsyeovil.com  
2a Kingfisher Close  
Gazelle Road  
Lynx Trading Estate  
Yeovil  
Somerset  
BA20 2PJ

Project:	Scale:	1:100 @ A1 / 1:200 @ A3	rev.	date	details	by	Key:
			A				
	Date:	July 2017	B				
			C				
	DWG No.	RDS_Shiles_P	D				
		E					
	Author:	James Kinnear	F				
			G				
Drawing:	Proposed Drawing Set	Client:		H			
				I			
				J			





Large plant  
lots on slabs

Grass

Driveway exit sensor for automatic opening of exit gates on car approach (buried magnetic option?)

VEHICLE  
DROP-OFF

BT Wall - stone/c  
tbc by client

Grass perimeter treatment - optional and at the client's discretion

Intercom linked to home/mobile phones w/ additional keypad and/or fobbed entry

ENTRANCE

Gravel  
Driveway

"Shiles Farm  
Carved into  
boulder



PLUMBING | HEATING | ELECTRICAL | RENEWABLE ENERGY


2a Kingfisher Close  
Gazelle Road  
Lynx Trading Estate  
Yeovil  
Somerset  
BA20 2PJ

Project:	Scale:	1:100 @ A1	rev.	date	details	by	Key:
			A				
	Date:	May 2018	B				
			C				
	DWG No.	RDS_Shiles_S2	D				
			E				
	Author:	James Kinnear	F				
Drawing: Proposed Site Plan	Client:		G				
			H				
			I				
			J				









# SECTION

## Materials Key:

- 1 - 100mm existing rigid PIR insulation

2 - Existing timber 100mm rafters.

3 - Existing 12.5mm plasterboard, skimmed and painted.

4 - 22mm T&G chipboard flooring.

5 - Instacoustic floating floor system or similar.

6 - Existing floorboards.

7 - Existing 200mm solid timber floor joists.

8 - Existing lathe and plaster ceiling.

9 - 12.5mm Gyproc Fireline board.

10 - IN10 acoustic insulation.

11 - 2 layers of 12.5mm Gyproc Fireline.

12 - Isolation washer.

13 - Adjustable acoustic hanger.
- 14 - 100mm Rockwool insulation or similar.

15 - 50mm fibreglass or rockwool insulation between 75mm timber stud at 400 centres.

16 - 50mm fibreglass or rockwool insulation between existing 125mm timber stud.

17 - 2 layers of 15mm Gyproc Soundbloc.

18 - 75mm Isover APR 1200 acoustic insulation between existing 125mm timber stud.

19 - Gypframe RB1 resilient bar at 600 centres.

20 - Existing brick masonry cavity wall.

21 - Celotex PL4000 or similar composite board at 62.5mm thickness. (unless cavity has been filled with insulation previously, in which case not added)

22 - Preformed tread and nosing fitted with counter sunk screws and acoustic sealant at specific intervals (see Building Regulation notes for details.)

23 - InstaCoustic Sound Barrier with grooved section round nosing.

24 - Existing timber stairs.

25 - Countersunk head screws.

Project:	Scale:	1:25@ A1	Revisions:
	Date:	December 2016	
	DWG No.	RDS11B_16_BR	
	Author:	James Kinnear	
Drawing:	Building Regulation Section	Client:	